LC²MOS Quad SPST Switches

ADG201A/ADG202A

FEATURES
- 44V Supply Maximum Rating
- ±15V Analog Signal Range
- Low R_{ON} (60Ω)
- Low Leakage (0.5nA)
- Break Before Make Switching
- Extended Plastic Temperature Range (−40°C to +85°C)
- Low Power Dissipation (33mW)
- Available in 16-Lead DIP/SOIC and 20-Lead PLCC/LCCC Packages
- Superior Second Source:
  - ADG201A Replaces DG201A, HI-201
  - ADG202A Replaces DG202

FUNCTIONAL BLOCK DIAGRAMS



SWITCHES SHOWN FOR A LOGIC "1" INPUT

GENERAL DESCRIPTION

The ADG201A and ADG202A are monolithic CMOS devices comprising four independently selectable switches. They are designed on an enhanced LC²MOS process which gives an increased signal handling capability of ±15V. These switches also feature high switching speeds and low R_{ON}.

The ADG201A and ADG202A consist of four SPST switches. They differ only in that the digital control logic is inverted. All devices exhibit break before make switching action. Inherent in the design is low charge injection for minimum transients when switching the digital inputs.

www.DZTIC.com/ADI

PRODUCT HIGHLIGHTS

1. Extended Signal Range:
   These switches are fabricated on an enhanced LC²MOS process, resulting in high breakdown and an increased analog signal range of ±15V.
2. Single Supply Operation:
   For applications where the analog signal is unipolar (0V to 15V), the switches can be operated from a single +15V supply.
3. Low Leakage:
   Leakage currents in the range of 500pA make these switches suitable for high precision circuits. The added feature of Break before Make allows for multiple outputs to be tied together for multiplexer applications while keeping leakage errors to a minimum.

ADG201A IN	ADG202A IN	SWITCH CONDITION
0	1	ON
1	0	OFF

Table I. Truth Table

REV. A

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.
Tel: 617/329-4700 Fax: 617/326-8703 Twx: 710/394-6577
Telex: 924491 Cable: ANALOG NORWOODMASS

ADG201A/ADG202A—SPECIFICATIONS (V_{DD} = +15V, V_{SS} = −15V, unless otherwise specified)

Parameter	K Version 25°C	K Version −40°C to +85°C	B Version 25°C	B Version −40°C to +85°C	T Version 25°C	T Version −55°C to +125°C	Units	Test Conditions
ANALOG SWITCH								
Analog Signal Range	±15	±15	±15	±15	±15	±15	Volts	
R_{ON}	60		60		60		Ω typ	$-10V \leq V_S \leq +10V$
	90	145	90	145	90	145	Ω max	I_{DS} = 1.0mA
								Test Circuit 1
R_{ON} vs. V_D (V_S)	20		20		20		% typ	
R_{ON} Drift	0.5		0.5		0.5		%/°C typ	
R_{ON} Match	5		5		5		% typ	V_S = 0V, I_{DS} = 1mA
I_S (OFF)	0.5		0.5		0.5		nA typ	$V_D = \pm 14V$; $V_S \mp 14V$; Test Circuit 2
OFF Input Leakage	2	100	2	100	1	100	nA max	
I_D (OFF)	0.5		0.5		0.5		nA typ	$V_D = \pm 14V$; $V_S = \mp 14V$; Test Circuit 2
OFF Output Leakage	2	100	2	100	1	100	nA max	
I_D (ON)	0.5		0.5		0.5		nA typ	$V_D = \pm 14V$; Test Circuit 3
ON Channel Leakage	2	200	2	200	1	200	nA max	
DIGITAL CONTROL								
V_{INH}, Input High Voltage		2.4		2.4		2.4	V min	
V_{INL}, Input Low Voltage		0.8		0.8		0.8	V max	
I_{INL} or I_{INH}		1		1		1	μA max	
DYNAMIC CHARACTERISTICS								
t_{OPEN}	30		30		30		ns typ	
t_{ON}[1]	300		300		300		ns max	Test Circuit 4
t_{OFF}[1]	250		250		250		ns max	Test Circuit 4
OFF Isolation	80		80		80		dB typ	V_S = 10V(p-p); f = 100kHz
								R_L = 75Ω; Test Circuit 6
Channel-to-Channel Crosstalk	80		80		80		dB typ	Test Circuit 7
C_S (OFF)	5		5		5		pF typ	
C_D (OFF)	5		5		5		pF typ	
C_D, C_S (ON)	16		16		16		pF typ	
C_{IN} Digital Input Capacitance	5		5		5		pF typ	
Q_{INJ} Charge Injection	20		20		20		pC typ	R_S = 0Ω; C_L = 1000pF; V_S = 0V
								Test Circuit 5
POWER SUPPLY								
I_{DD}	0.6		0.6		0.6		mA typ	Digital Inputs = V_{INL} or V_{INH}
I_{DD}		2		2		2	mA max	
I_{SS}	0.1		0.1		0.1		mA typ	
I_{SS}		0.2		0.2		0.2	mA max	
Power Dissipation		33		33		33	mW max	

www.BDTIC.com/ADI

NOTES
[1]Sample tested at 25°C to ensure compliance.
Specifications subject to change without notice.

ABSOLUTE MAXIMUM RATINGS*

(T_A = +25°C unless otherwise stated)

V_{DD} to V_{SS} 44V
V_{DD} to GND 25V
V_{SS} to GND . . . . . −25V
Analog Inputs[1]
Voltage at S, D . . . . . V_{SS} −0.3V to V_{DD} +0.3V
Continuous Current, S or D 30mA
Pulsed Current S or D
1ms Duration, 10% Duty Cycle 70mA
Digital Inputs[1]
Voltage at IN . . . . . V_{SS} −2V to V_{DD} +2V or 20mA, Whichever Occurs First

Power Dissipation (Any Package)
Up to +75°C 470mW
Derates above +75°C by . . . . . 6mW/°C
Operating Temperature
Commercial (K Version) . . . . . −40°C to +85°C
Industrial (B Version) . . . . . −40°C to +85°C
Extended (T Version) . . . . . −55°C to +125°C
Storage Temperature Range . . . . . −65°C to +150°C
Lead Temperature (Soldering 10sec) . . . . . +300°C

NOTE
[1]Overvoltage at IN, S or D will be clamped by diodes. Current should be limited to the Maximum Rating above.

*COMMENT: Stresses above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability. Only one Absolute Maximum Rating may be applied at any one time.

CAUTION

ESD (electrostatic discharge) sensitive device. The digital control inputs are diode protected; however, permanent damage may occur on unconnected devices subject to high energy electrostatic fields. Unused devices must be stored in conductive foam or shunts. The protective foam should be discharged to the destination socket before devices are removed.

ORDERING GUIDE

Model[1]	Temperature Range	Package Option[2]
ADG201AKN	−40°C to +85°C	N-16
ADG201AKR	−40°C to +85°C	R-16A
ADG201AKP	−40°C to +85°C	P-20A
ADG201ABQ	−40°C to +85°C	Q-16
ADG201ATQ	−55°C to +125°C	Q-16
ADG201ATE	−55°C to +125°C	E-20A
ADG202AKN	−40°C to +85°C	N-16
ADG202AKR	−40°C to +85°C	R-16A
ADG202AKP	−40°C to +85°C	P-20A
ADG202ABQ	−40°C to +85°C	Q-16
ADG202ATQ	−55°C to +125°C	Q-16
ADG202ATE	−55°C to +125°C	E-20A

NOTES
[1]To order MIL-STD-883, Class B processed parts, add/883B to T grade part numbers. See Analog Devices Military Products Databook (1990) for military data sheet.
[2]E = Leadless Ceramic Chip Carrier (LCCC); N = Plastic DIP; R = 0.15" Small Outline IC (SOIC); P = Plastic Leaded Chip Carrier (PLCC); Q = Cerdip.

PIN CONFIGURATIONS

www.BDTIC.com/ADI

DIP, SOIC



LCCC



PLCC



ADG201A/ADG202A FUNCTIONAL DIAGRAM





Figure 1. Typical Digital Input Cell

ADG201A/ADG202A—Typical Performance Characteristics

The switches are guaranteed functional with reduced single or dual supplies down to 4.5V.



R_{ON} as a Function of V_D (V_S): Dual Supply Voltage



R_{ON} as a Function of V_D (V_S): Single Supply Voltage



Leakage Current as a Function of Temperature (Note: Leakage Currents Reduce as the Supply Voltages Reduce)



Trigger Level vs. Power Supply Voltage: Dual or Single Supply Voltage

www.BDTIC.com/ADI



Switching Time vs. Supply Voltage (Dual Supply)



Switching Time vs. Supply Voltage (Single Supply)



Test Circuit 1



Test Circuit 2



Test Circuit 3





www.BDTIC.com/ADI

Test Circuit 4





Test Circuit 5. Charge Injection



Test Circuit 6. Off Isolation



Test Circuit 7. Channel-to-Channel Crosstalk

TERMINOLOGY

R_{ON}	Ohmic resistance between terminals OUT and S
R_{ON} Match	Difference between the R_{ON} of any two channels
I_S (OFF)	Source terminal leakage current when the switch is off
I_D (OFF)	Drain terminal leakage current when the switch is off
I_D (ON)	Leakage current that flows from the closed switch into the body
V_D (V_S)	Analog voltage on terminal D, S
C_S (OFF)	Switch input capacitance "OFF" condition
C_D (OFF)	Switch output capacitance "OFF" condition
C_{IN}	Digital input capacitance
C_D, C_S (ON)	Input or output capacitance when the switch is on
t_{ON}	Delay time between the 50% and 90% points of the digital input and switch "ON" condition
t_{OFF}	Delay time between the 50% and 90% points of the digital input and switch "OFF" condition
t_{OPEN}	"OFF" time measured between 50% points of both switches, which are connected as a multiplexer, when switching from one address state to another
V_{INL}	Maximum Input Voltage for a Logic Low
V_{INH}	Minimum Input Voltage for a Logic High
I_{INL} (I_{INH})	Input current of the digital input
V_{DD}	Most positive voltage supply
V_{SS}	Most negative voltage supply
I_{DD}	Positive supply current
I_{SS}	Negative supply current

MECHANICAL INFORMATION

OUTLINE DIMENSIONS

Dimensions shown in inches and (mm).

16-Pin Plastic (N-16)



16-Pin Cerdip (Q-16)



www.DZTIC.com/ADI

SOIC Package (R-16A)



20-Terminal Leadless Ceramic Chip Carrier (E-20A)



20-Terminal Plastic Leaded Chip Carrier (P-20A)